



INDUSTRIAL COMPUTER

RCO-6000-KBL-1050TI

Industrial GPU Computer with 6th/7th Gen Intel® Core™ Processor And Q170 PCH, GTX 1050 TI Integrated



Features

- LGA 1151 socket for 6th or 7th Gen. Intel® Core™ i7/i5/i3 or Pentium® / Celeron® desktop processor with Q170 chipset
- NVIDIA GeForce® GTX 1050 Ti Graphics engine based on NVIDIA Pascal™ GPU architecture
- 2x 260-pin DDR4 SODIMM. max up to 32GB
- 6x display interface supported by 2x DVI-I, 3x DisplayPort, 1x HDMI
- 2x Intel® GbE supporting Wake-on-LAN and PXE
- 4x 2.5" SATA HDD bay and 2x mSATA supporting RAID 0, 1, 5, 10
- 4x full-size mini PCIe for communication or expansion modules, 4x SIM socket
- 4x RS-232/422/485 (w/ 2x internal), 6x USB 3.0, 2x USB 2.0
- 8x DI + 8x DO with isolation
- 9 to 48VDC wide range power input supporting AT/ATX mode
- -25°C to 60°C extended operating temperature
- Includes 220W power adapter

Specifications

System	
Processor	Support 6th & 7th Gen Intel® Core™ i7 / i5 / i3 / Pentium® / Celeron® Desktop Processor (LGA 1151)
	<ul style="list-style-type: none"> • 7th Gen Intel® Core™ i7-7700T, Quad Core, 8MB cache, up to 3.8 GHz • 7th Gen Intel® Core™ i5-7500T, Quad Core, 6MB cache, up to 3.3 GHz • 7th Gen Intel® Core™ i3-7101TE, Dual Core, 3MB Cache, 3.4 GHz • 6th Gen Intel® Core™ i7-6700TE, Quad Core, 8MB Cache, up to 3.4 GHz • 6th Gen Intel® Core™ i5-6500TE, Quad Core, 6MB Cache, up to 3.3 GHz • 6th Gen Intel® Core™ i3-6100TE, Dual Core, 4MB Cache, 2.7 GHz • Intel® Pentium® G4400TE, Dual Core, 3MB Cache, 2.4 GHz • Intel® Celeron® G3900TE, Dual Core, 2MB Cache, 2.3 GHz
System Chipset	Intel® Q170 Express Chipset
LAN Chipset	<ul style="list-style-type: none"> • GbE1: Intel® I210-AT (Support Wake-on-LAN and PXE) • GbE2: Intel® I219LM (Support Wake-on-LAN and PXE)
Audio Codec	Realtek ALC888S
System Memory	2x 260-Pin DDR4 1866/2133MHz SODIMM. Max. up to 32GB
Graphics	Intel® HD Graphics 530 / 630 or NVIDIA GeForce® GTX 1050 Ti
BIOS	AMI 128Mbit SPI BIOS
Watchdog	Software Programmable Supports 1~255 sec. System Reset
TPM	TPM 1.2
Display	
Display Port	3x DP
DVI	2x DVI-I
HDMI	1x HDMI
Multiple Display	6 Display Interfaces
Storage	
mSATA	2x mSATA (shared by 2x Mini PCIe)
SIM Socket	2x External SIM socket 2x Internal SIM Socket
SSD/HDD	2x Internal 2.5" SATA HDD Bay 2x Hotswap 2.5" SATA HDD Bay Support RAID 0, 1, 5, 10
Expansion	
Mini PCIe	4x Full-size Mini PCIe
I/O	
Audio	1x Mic-in, 1x Line-out
COM	2x RS-232/422/485 2x RS-232/422/485 (Internal)
DIO	8 in / 8 out (Isolated)
LAN	2x GbE RJ45
Universal I/O Bracket	2x Universal I/O Bracket (Base Model)
USB	6x USB 3.0, 2x USB 2.0
Others	4x WiFi Antenna Holes 1x Power Switch, 1x AT/ATX Switch, 1x Remote Power On/Of
Operating System	
Windows	6th Gen CPU: Windows 10, Windows 7, WES7 7th Gen CPU: Windows 10
Linux	Linux kernel 4.X
Power	
Power Adapter	DC 9 ~ 48 VDC
Power Mode	AT/ATX selectable
Power Supply Voltage	9~48VDC
Power Connector	3-pin Terminal Block



Power Protection	Over-Voltage Protection (OVP) Over-Current Protection (OCP) Reverse Polarity Protection (RPP)
------------------	---

Environment	
Operating Temperature	-25°C to 60°C
Storage Temperature	-40°C to 85°C
Relative Humidity	10% to 95% (non-condensing)
Certification	CE, FCC Class A
Vibration	with SSD: 5 Grms, 5 - 500 Hz, 0.5 hr/axis with HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis
Shock	with SSD: 50G, half sine, 11ms
Physical	
Dimensions	240 (W) x 261(D) x 127 (H) mm
Construction	Extruded aluminum with heavy duty metal
Mounting Options	Wall Mounting

External I/O Mechanical Layout


Front Panel

Rear Panel



Dimension

Unit: mm



Available Models

Model No.	Description
RCO-6000-KBL-2C-1050TI-P	Industrial GPU Computer with 6th/7th Gen Intel® Core™ Processor And Q170 PCH, GTX 1050 TI Integrated

Optional Accessories

Model No.	Description
1-E09A22801	Adapter AC/DC 24V/11.67A 280W with 3pin Terminal Block Plug 5.0mm Pitch
1-E09A22102	Adapter AC/DC 24V 9.2A 220W with 3pin Terminal Block Plug 5.0mm Pitch
999930	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm

Packing List

- 1x RCO-6000-CFL-8NS
- 1x Utility DVD Driver
- 1x Wall Mount Kit
- 1x Accessory Kit

Compliances and Standards

Shock	with SSD: 50G, half sine, 11ms IEC60068-2-27:2008 Designed to comply with MIL-STD-810G Method 516.7 Procedure I
Vibration	with SSD: 5 Grms, 5 - 500 Hz, 0.5 hr/axis with HDD: 1 Grms, 5 - 500 Hz, 0.5 hr/axis IEC60068-2-64:2008 Designed to comply with MIL-STD-810G Method 514.7 Procedure I
Operating Temperature	-25°C to 60°C IEC60068-2-1:2007 (Cold test procedure) IEC60068-2-2:2007 (Dry heat test procedure) IEC60068-2-3:2007 (Damp heat, steady state, test procedure) IEC60068-2-14:2009 (Wide temperature range thermal shock)
EMI	<ul style="list-style-type: none"> • FCC Class A (47 CFR part 15.109 and part 15.107) • CE • ICES-003 • UKCA

Exports And Tariff Codes

ECCN	5A992.c
HTS	8471.50.0150
ScheduleB	84.71