



AI EDGE INFERENCE COMPUTER

# RCO-6000-RPL-8NS

AI Edge Industrial Computer with LGA 1700 for Intel® Core™ (Series 2) / 14th / 13th / 12th Gen Processors & R680E PCH, 8x U.2 7mm NVMe, Software RAID

## Features

- Intel® Core™ Processors (BTL, Series 2) / 14th / 13th / 12th Gen RPL/ADL Series, LGA1700
- Intel® R680E Chipset
- 2x DDR5 4800/5600 MT/s SODIMM. Max. up to 96GB
- Triple Independent Display: 2x DisplayPort, 1x DVI-I
- 2x Intel® 2.5 GbE supporting Wake-on-LAN and PXE
- 1x Full-size Mini PCIe for communication or expansion modules, 2x SIM socket
- 8x 7mm Hot-swappable U.2 NVMe SSD Module with RAID 0, 1, 5, 10
- 1x 9mm 2.5" SATA SSD (Internal), 1x 7mm 2.5" SATA SSD (Hot-swap)
- 1x M.2 (E Key, PCIe x1, USB 2.0, 2230)
- 1x M.2 (B Key, 2242/3042/3052, PCIe x2, Support AI Module/NVMe Storage, PCIe x1 & USB 3.2 Gen1, Support 4G/5G)
- 6x RS-232/422/485 (4x internal), 8x USB 3.2 Gen 2, 1x USB 3.2 Gen 1 (internal)
- 9 to 48VDC Wide Range Power Input Supporting AT/ATX Mode
- Wide Operating Temperature -25°C up to 60°C
- TPM 2.0 Supported



## Specifications

### System

Processor	13th Gen Intel® Core™ Processors (Raptor Lake-S)
Standard	- Intel® Core™ i7-13700TE, 35W
	- Intel® Core™ i5-13500TE, 35W
	12th Gen Intel® Core™ Processors (Alder Lake-S)
	- Intel® Core™ i7-12700TE, 35W
	- Intel® Core™ i5-12500TE, 35W

Project Based	- Intel® Core™ 3 / 5 / 7 (Series 2, Bartlett Lake-S, 45W)
	- 14th Gen Intel® Core™ i3 / i5 / i7 / i9 (Raptor Lake-S Refresh, 35W~65W)
	- 13th Gen Intel® Core™ i3 / i5 / i7 / i9 (Raptor Lake-S, 35W~65W)
	- 12th Gen Intel® Core™ i3 / i5 / i7 / i9 (Alder Lake-S, 35W~65W)

System Chipset	Intel® R680E Express Chipset
LAN Chipset	2.5 GbE1: Intel I226, 2.5 GbE2: Intel I226 Support Wake-on-LAN and PXE, Support TSN
Audio Codec	Realtek ALC888S
System Memory	2x 262-Pin DDR5 4800/5600 MT/s SODIMM. Max. up to 96GB (ECC and Non-ECC)
Graphics	Intel® UHD Graphics 770/710
BIOS	AMI 256Mbit SPI BIOS
Watchdog	Software Programmable Supports 1~255 sec. System Reset
AI Accelerator	Supports 3x Hailo-8™ modules
TPM	TPM 2.0

### Display

Display Port	2x DisplayPort 1.4a, Support resolution 5120 x 3200, Up to 7680 x 4320
DVI	1x DVI-I, support resolution 1920 x 1200
VGA	Yes (by optional split cable)
Multiple Display	Triple Display

### Storage

M.2	1x M.2 B Key, 2242/3042/3052 (PCIe x2, Support AI Module/NVMe Storage) (PCIe x1 & USB 3.2 Gen1, Support 4G/5G)
mSATA	1x mSATA (Shared by 1x Mini PCI Express)
NVMe	2x Removable Cannister Bricks with 2.5" 8 Bay U.2 NVMe SSD (Support H=7mm)
SIM Socket	2x External SIM socket (Mini PCIe/M.2 B Key attached)
SSD/HDD	1x 9mm 2.5" SATA HDD Bay (Internal) 1x 7mm 2.5" SATA HDD Bay (Hot-swappable) 8x 7mm 2.5" NVMe SSD Bay (Hot-swappable) Support RAID 0, 1, 5, 10

### Expansion

M.2	1x M.2 (E Key, PCIe x1, USB 2.0, 2230)
Mini PCIe	1x Full-size Mini PCIe (1x shared by 1x mSATA)

Expansion Modules	2x EDGEBoost I/O Brackets:
	• 4-port GbE module with Intel® I350 Chipset, RJ-45/M12 connector (PoE optional)
	• 2-Port RJ45 10GbE with Intel X710 Chipset
	• 4-Port USB 3.0 (share PCIe Gen2 x1 bandwidth)
	• 1x M.2 B-Key, 2242 for AI/NVMe, 1x M.2 B-Key, 3042/3052 for 5G/AI/NVMe
	• 1x M.2 M-Key, PCIe x4 Lane, 2242/2260 for AI Module/NVMe
	• 1x M.2 for 5G (B Key, PCIe x1, USB 3.0, 3042/3052), 2x SIM socket, 1x SIM switch

### I/O

Audio	1x Mic-in, 1x Line-out
CAN	2x CAN 2.0 A/B 2-pin Internal header

COM	2x RS-232/422/485 ; 4x RS-232/422/485 (Internal)
DIO	8 in / 8 out (Isolated)
EDGEBoost I/O Bracket	2x EDGEBoost I/O Bracket (By mini PCIe interface)
LAN	2x RJ45
USB	8x USB 3.2 Gen 2 (10 Gbps) 1x USB 3.2 Gen 1 (5 Gbps, 1x Internal), 2x USB 2.0 (Internal)
Others	5x WiFi Antenna Holes 1x Power Switch, 1x AT/ATX Switch, 1x Remote Power On/Off 1x PC/Car Mode Switch, 1x Delay Time Switch 1x Removable CMOS Battery

### Operating System

Windows	Windows 10/11
Linux	Linux kernel

### Power

Power Adapter	Optional AC/DC 24V/9.2A, 220W Optional AC/DC 24V/11.67A, 280W (GPU/Card Expansion) Optional AC/DC 24V/15A, 360W (i7/i9 CPU/GPU/Card Expansion)
Power Mode	AT, ATX
Power Ignition Sensing	Power Ignition Management
Power Supply Voltage	9~48VDC 12~48VDC for NVMe EDGEboost Node
Power Connector	5-pin Terminal Block 4-pin Terminal Block for NVMe EDGEBoost Node (12V requires 4-pin terminal block)
Power Protection	OVP (Over Voltage Protection) OCP (Over Current Protection) Reverse Protection

### Environment

Operating Temperature	-25°C to 60°C
Storage Temperature	-30°C to 85°C
Relative Humidity	10% to 95% (non-condensing)
Certification	UL 62368 Ed. 3, CE, FCC Class A
Vibration	With HDD: 1 Grms (5 - 500 Hz, 0.5 hr/axis) With SSD: 3 Grms (5 - 500 Hz, 0.5 hr/axis)
Shock	With SSD: 50G half-sin 11ms

### Physical

Dimensions	240 (W) x 261 (D) x 166.9 (H) mm
Weights	10.5 ~ 11.5 kg
Construction	Extruded Aluminum with Heavy Duty Metal
Mounting Options	Wall Mounting


\* Processor Base Power: 35W, 45W, 60W, 65W (CPU-dependent); View appendix for complete supported processors table.

\*\* For 12/13/14th Gen Intel CPUs configured to run at 65W, operating temperatures will be limited to 45°C.


\*\*\* 65W CPUS may experience thermal throttling depending on extreme application workloads; this is also due to an increase in the physical CPU cores from the Intel silicon (up to 24 cores). Please note, this does not indicate system malfunction or problems in the fanless design. Please consult our embedded engineers for the best configuration to match your application requirements.

\*\*\*\* All specifications and photos are subject to change without notice.

## External I/O Mechanical Layout




### Available EDGEBoost I/O



## Dimension

Unit: mm



## Compatible GPU AVL

Model	RAM	CUDA Cores	TDP	TOPS/TFLOPS	Displays	System Interface	Form Factor
NVIDIA T1000	8G	896	50W	5.3 TFLOPS	4x mDP	PCIe 3.0 x16	2.7" H x 6.1" L, Low-Profile Single Slot
NVIDIA RTX A1000	8G	2304	50W	6.74 TFLOPS	4x mDP	PCIe 4.0 x8	2.7" H x 6.4" L, Single slot
NVIDIA RTX A2000	12G	3328	70W	7.99 TFLOPS	4x mDP	PCIe 4.0 x16	2.7" H x 6.6" L, Low Profile, Dual Slot
NVIDIA RTX 2000 ADA	16G	2816	70W	12 TFLOPS	4x mDP	PCIe 4.0 x8	2.7" H x 6.6" L, Dual slot
NVIDIA RTX 4000 SFF ADA	20G	6144	70W	19.2 TFLOPS	4x mDP	PCIe 4.0 x16	2.7" H x 6.6" L, Low Profile, Dual Slot

## Available Models

Model No.	Description
RCO-6000-RPL-8NS-P	AI Edge Inference Computer with LGA 1700 for Intel® Core™ (Series 2) / 14th / 13th / 12th Gen Processors & R680E PCH, 2x LAN, 8x U.2 7mm NVMe, Software RAID

## Optional Accessories

Model No.	Description
1-E09A22102	Adapter AC/DC 24V 9.2A 220W with 3pin Terminal Block Plug 5.0mm Pitch
1-E09A22801	Adapter AC/DC 24V/11.67A 280W with 3pin Terminal Block Plug 5.0mm Pitch
1-E09A36002	Adapter AC/DC 48V/7.5A 360W with 3pin Terminal Block Plug 5.0mm Pitch
999930	Power Cord, 3-pin US Type, 180cm
1-TPCD00002	Power Cord, European Type, 180cm
1-TPCD00001	Power Cord, 3-pin UK Type, 180cm

## Packing List

1x RCO-6000-RPL-8NS  
 1x Wall Mount Kit  
 1x Accessory Kit  
 1x DVI to VGA Adapter

## Exports And Tariff Codes

ECCN	5A992.c
HTS	8471.50.0150
ScheduleB	84.71

## Compliances and Standards

Vibration	With HDD: 1 Grms (5 - 500 Hz, 0.5 hr/axis) With SSD: 3 Grms (5 - 500 Hz, 0.5 hr/axis) IEC60068-2-64:2008 Designed to comply with MIL-STD-810H Method 514.8 Procedure I
Shock	With SSD: 50G half-sin 11ms IEC60068-2-27:2008 Designed to comply with MIL-STD-810H Method 516.8 Procedure I
Operating Temperature	-25°C to 60°C IEC60068-2-1:2007 (Cold test procedure) IEC60068-2-2:2007 (Dry heat test procedure) IEC60068-2-3:2007 (Damp heat, steady state, test procedure) IEC60068-2-14:2009 (Wide temperature range thermal shock)
EMC	<ul style="list-style-type: none"> <li>• FCC Class A</li> <li>• CE</li> <li>• ICES-003</li> <li>• UKCA</li> <li>• Industrial EMC Compliance</li> <li>- EN 61000-4-2: 2009</li> <li>- EN IEC 61000-4-3: 2020</li> <li>- EN 61000-4-4: 2012</li> <li>- EN 61000-4-5: 2014 +A1: 2017</li> <li>- EN 61000-4-6: 2014</li> </ul>
Safety	<ul style="list-style-type: none"> <li>• UL Safety: UL62368-1, 3rd Ed., (cULus)</li> <li>• Test procedure: CB Scheme</li> <li>• Standard: IEC 62368-1:2018</li> </ul>